

MODEL NO.	MAIN - AL CONDUCTOR (mm ²) Al & ACSR	TAP - AL. CONDUCTOR (mm ²) Al / ACSR / Cu	WEIGHT KG/100 PCS.
CN - 3	25 - 185	16 - 95	38

STANDARD : CURRENT CYCLE TESTS, HEAVY DUTY (CLASS A) IN ACCORDANCE WITH ANSI C119.4 - 2004

MATERIALS


- 1. BODY : ALUMINIUM ALLOY
- 2. KEEPER : ALUMINIUM ALLOY
- 3. TAP EYE BOLT : TIN PLATED BRONZE
- 4. EYE SCREW : BRONZE
- 5. SPRING WASHER : STAINLESS STEEL

ATTN: K. In-50
(2) 2425814-18

BODY MARKING : APPLICABLE CONDUCTOR TYPE AND SIZE, MANUFACTURER'S SYMBOL

© 2008

MAX. TORQUE APPLYING 240 LB-IN. (RECOMMENDED 200 - 220 LB - IN)

DRAWN BY	NAME <i>[Signature]</i>	DATE 27/6/48	 CHAINANT INDUSTRY CO., LTD	
CHECKED BY	<i>[Signature]</i>	27/6/48		
APPROVE BY	<i>[Signature]</i>	27/6/48		
SCALE	HOT LINE PROTECTED THREAD CLAMP	MAT. - AL - A 356.2 - BRONZE	USE ON	DRAW.NO. 6-941-3